


BRANCH OUTLETS / Style 87G

QUIK-T™ BRANCH OUTLETS

Maximum working pressure: 300 psi
For fire protection equipment and approved pressure ratings please contact Modgal.

STYLE 87G

Cross Grooved



Nominal Size (Inches / DN)		Pipe Outside Diameter	Outlet Size	Quik-T™ Dimensions			Hole Diameter Tolerance +1/8"	Bolts			Weight Lbs	Approvals
Run	Outlet			A	B	C		Qty.	Size	Length		
2" / 50	1¼" / 32	2.375	1¼"	3.01	5.31	3.23	1¾"	2	3/8"	2¼"	4.31	FM / UL / LPCB / VDS
	1½" / 40	2.375	1½"	3.01	5.31	3.23	1¾"	2	3/8"	2¼"	4.35	FM / UL / LPCB / VDS
2½" / 65	1¼" / 32	2.875	1¼"	3.23	5.91	3.62	2"	2	½"	3"	4.74	FM / UL
	1½" / 40	2.875	1½"	3.23	5.91	3.62	2"	2	½"	3"	5.12	FM / UL
3" OD	1¼" / 32	3.000	1¼"	3.23	5.91	3.62	2"	2	½"	3"	4.75	FM / UL / LPCB / VDS
	1½" / 40	3.000	1½"	3.23	5.91	3.62	2"	2	½"	3"	5.11	FM / UL / LPCB / VDS
3" / 80	1¼" / 32	3.500	1¼"	3.74	6.30	3.74	2"	2	½"	3"	5.62	FM / UL / LPCB / VDS
	1½" / 40	3.500	1½"	3.74	6.30	3.70	2"	2	½"	3"	5.82	FM / UL / LPCB / VDS
	2" / 50	3.500	2"	3.66	6.30	4.13	2½"	2	½"	3"	5.31	FM / UL / LPCB / VDS
4" / 100	1¼" / 32	4.500	1¼"	4.09	7.36	3.78	2"	2	½"	3"	6.13	FM / UL / LPCB / VDS
	1½" / 40	4.500	1½"	4.09	7.36	3.78	2"	2	½"	3"	6.16	FM / UL / LPCB / VDS
	2" / 50	4.500	2"	4.09	7.36	4.21	2½"	2	½"	3"	7.09	FM / UL / LPCB / VDS
	2½" / 65	4.500	2½"	4.09	7.36	4.17	2¾"	2	½"	3"	7.88	FM / UL
	3" OD	4.500	3" OD	4.09	7.36	4.17	2¾"	2	½"	3"	7.88	FM / UL / VDS
5" OD	3" / 80	4.500	3"	4.45	7.36	5.12	3½"	2	½"	3"	12.26	FM / UL / VDS
	1¼" / 32	5.500	1¼"	4.69	8.50	3.94	2"	2	5/8"	3½"	8.78	FM / VDS
	1½" / 40	5.500	1½"	4.69	8.50	3.94	2"	2	5/8"	3½"	8.95	FM / VDS
6" / 150	2" / 50	5.500	2"	4.69	8.50	4.17	2½"	2	5/8"	3½"	9.48	FM / VDS
	3" OD	5.500	3" OD	4.69	8.50	4.21	2¾"	2	5/8"	3½"	10.15	FM / VDS
	1¼" / 32	6.625	1¼"	5.24	9.65	3.78	2"	2	5/8"	4¾"	9.33	FM / UL / LPCB / VDS
	1½" / 40	6.625	1½"	5.14	9.65	3.78	2"	2	5/8"	4¾"	9.55	FM / UL / LPCB / VDS
	2" / 50	6.625	2"	5.18	9.65	4.21	2½"	2	5/8"	4¾"	10.84	FM / UL
	2½" / 65	6.625	2½"	5.22	9.65	4.21	2¾"	2	5/8"	4¾"	11.36	FM / UL / LPCB / VDS
	3" OD	6.625	3" OD	5.22	9.65	4.21	2¾"	2	5/8"	4¾"	11.36	FM / UL / LPCB / VDS
8" / 200	3" / 80	6.625	3"	5.45	9.72	5.51	3½"	2	5/8"	4¾"	15.91	FM / UL / VDS
	4" / 100	6.625	4"	5.49	9.72	6.42	4½"	2	5/8"	4¾"	13.77	FM / UL / LPCB / VDS
	2½" / 65	8.625	2½"	6.10	12.60	4.72	2¾"	2	¾"	4¾"	13.75	-
	3" OD	8.625	3" OD	6.10	12.60	4.72	2¾"	2	¾"	4¾"	13.75	-
	3" / 80	8.625	3"	6.34	12.60	5.43	3½"	2	¾"	4¾"	16.83	VDS
	4" / 100	8.625	4"	6.34	12.60	6.46	4½"	2	¾"	4¾"	17.19	VDS